



Top Gasoline

Product Sheet

Top Gasoline is a multifunctional additive compatible with all types of petrol, designed for engines with traditional PFI fuel systems and with carburetors. Provides high detergent power for cleaning and maintaining the efficiency of the entire fuel system.

The clogging of the injectors leads to a poor quality of fuel atomization, resulting in an irregular flow to the engine. Deposits can also cause the valves to stick, thus altering the correct fuel/air ratio and therefore the combustion efficiency.

When the fuel system gets dirty, not only does the engine performance decrease in terms of driveability and response, but there is also higher fuel consumption and particulate emissions.

Top Gasoline contains a special package of detergent and dispersing substances that allow the deposits to be effectively removed from the first treatment, restoring the regular fuel supply to the combustion chamber and consequently the energy efficiency of the engine.

Its use, continuous or periodic, allows to keep the fuel system clean, preventing the accumulation of dirt on injectors, valves and carburetors, thus avoiding the progressive decline in engine performance. In this way it prevents the increase in polluting emissions and improves fuel economy.

Thanks to its formulation containing anti-friction additives and octane booster, it allows an increase in engine power while reducing wear.

At the same time it protects all system parts from rust and corrosion, counteracting the harmful effects caused by small quantities of water that may be present.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



Top Gasoline

Product Sheet

PROPERTIES

- Clean-up performance: eliminates deposits from injectors, valves and carburetors, restoring engine performance
- Keep clean performance: keeps the fuel system clean and lubricated
- Lowers fuel consumption and polluting emissions
- Protects the fuel system from rust and corrosion
- Contains Friction Modifier: improves lubrication and helps control engine wear
- Contains Octane Booster: improves combustion and increases power

DIRECTIONS FOR USE

A 250 ml package treats about 50-60 liters of gasoline.
For better mixing with the fuel, it is recommended to pour the additive into the tank just before refueling.

RECOMMENDED USE

To protect the fuel system from the accumulation of deposits and keep it efficient over time, carry out a treatment every 2 – 3 tanks of fuel or at least every 4.000 – 5.000 km. To carry out a complete cleaning, especially in case of persistent deposits and/or decline in engine performance, it is possible to carry out two consecutive treatments without contraindications.

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio