



Hot Fuel

Product Sheet

Hot Fuel is a preventive anti-freezing treatment for diesel fuels, especially formulated to improve the performances of diesel fuels and combustible diesel oils at low temperatures.

ADVANTAGES

- Prevents formation of paraffin crystals in diesel oil, thus permitting an excellent filterability of fuel and a good engine start even at very low temperatures.
- Helps keeping the supply system lubricated and protected.
- Depending on dosage and type of diesel fuel, it permits starts at temperatures down to -25°C .
- Improves the fluidity of diesel oil at cold starts.

DIRECTIONS FOR USE

In order to make blending easier, pour your additive into the tank immediately before refuelling. If you wish to obtain the best performances, it is advisable to use your additive at a fuel temperature not lower than $5-7^{\circ}\text{C}$. Shake the bottle well before using.

1 liter, 25 liter and 200 liter packaging:

We suggest a 0.2 – 0.3 % rate (2-3 liter of additive per 1000 liter diesel oil)

250 ml. single-dose packaging:

250 ml additive treat a full tank of fuel (approximately 50 liter)

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio