



Product Sheet

VBA Synt is a superior performance lubricant that offers a great flexibility of employment: it was developed for a wide range of 2-stroke motors installed on scooters, motorcycles, small commercial vehicles and gardening equipment in general.

VBA Synt is formulated with special components that assure an efficient lubrication all the time and also an excellent and clean combustion without deposits.

Its additives with a *low ash* content and a very good deterging power permit to maintain clean all the hottest parts of the thermal group, thus avoiding the accumulation of deposits on the sparking-plug and between the piston groove and the piston ring.

VBA Synt contains the exclusive BARDAHL POLAR PLUS formula that forms a lubricant molecular film that strongly adheres on the metal surface and creates a lasting protection barrier, drastically reducing friction and wear on all the lubricated parts of the engine.

PROPERTIES

- Best protection against wear and seizure.
- Better cleanliness of the engine and sparking-plug.
- Reduces exhaust smoke.
- Utmost flexibility of employment.

VBA Synt is suitable for automatic mixing systems and for manual mixing at 2% or according to the manufacturer's directions.





Product Sheet

PERFORMANCE LEVEL

API TC

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity a 40°C	99,5 cSt
Viscosity a 100°C	12,4 cSt
Density a 15°C	0,873 kg/l
Pour Point	-15°C
Flash Point	115°C
Ashes	0,09%

The values mentioned in this table are only indicative and may vary within certain tolerances

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.