



SYNTHETIC SPECIAL OIL 2-STROKE

Product Sheet

KXT Racing is a technologically advanced motor-oil with excellent performances, especially developed for racing 2-stroke motorcycles.

Its revolutionary formulation starts a new generation of synthetic oils.

Contains the **BARDAHL POLAR PLUS** formula, that - together with special synthetic esters - gives this oil a better adhesiveness to metal surfaces. This assures the best anti-seizure safety even under the most severe working conditions of the engine and reduces friction among the motor parts, thus increasing its power.

KXT Racing is formulated with particular additives at low ash content, which ensure maximum protection and a better engine cleanliness.

KXT Racing is 100% synthetic and thanks to its concentrated formula can be employed at a low dosage.

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity Grade	SAE 60
Viscosity a 40°C	208,4 cSt
Viscosity a 100°C	22,5 cSt
Density a 15°C	0,905 kg/l
Flash Point	205°C
Pour Point	-21°C
Ashes	0,12%

The values shown in this table are just as an indication, variable within certain tolerances.

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio