



KGR INJECTION

SYNTHETIC SPECIAL OIL 2-STROKE

Product Sheet

KGR Injection is a **premium performance** lubricant especially developed for high performance motorcycle 2-stroke engines, snowmobiles and scooters. It is ideal for automatic lubrication systems and DFI systems. Also suitable for manual blending, to be done following the manufacturer's directions.

KGR Injection is formulated with special high viscosity synthetic bases and this ensures a constantly effective lubrication and at the same time an excellent and clean combustion without deposits.

This formula contains *low ash* additives that have been recently developed and have a high cleansing power: these permit to maintain clean all the warmest parts of the thermal unit and avoid the accumulation of deposits that tend to block the piston rings in the ring sticks and cause irregular wear in the cylinder.

KGR Injection contains the exclusive BARDHAL POLAR PLUS anti-friction formula that is able to build a molecular lubricating film that chemically settles on metal, creates a permanent protecting barrier and efficiently reduces friction and wear on all lubricated parts.

PROPERTIES

- Best protection against wear and seizure.
- Best protection of crankshaft, connecting rod and bearings.
- More power and better performance of the engine.
- Perfect cleanliness of engine and sparking plug.
- "Low ash" formula: reduces the deposits of high temperature, it is extremely compatible with catalyzers.
- Reduces a lot the exhaust smokiness.
- Very easy pumping at low temperatures.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



KGR INJECTION

SYNTHETIC SPECIAL OIL 2-STROKE

Product Sheet

PERFORMANCE LEVEL

API TC, JASO FD, ISO-L-EGD

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity at 40°C	75,3 cSt
Viscosity at 100°C	11,4 cSt
Density at 15°C	0,868 kg/l
Pour point	-39°C
Flash point	90°C
Ashes	0,17%

The values shown in this table are just as an indication, variable within certain tolerances.

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio