



ADVANCED SYNTHETIC BLEND

Product Data Sheet

Premium Quality lubricants, totally synthetic, formulated for most of 4-stroke Hypersport, Sport-Tourer and Off-Road motorcycle engines, with both integrated and separate gearbox, with wet or dry clutch.

Developed to offer the best performance in all driving conditions and in any type of engine, they always guarantee maximum engine protection even under extreme stress circumstances.

Containing the exclusive Bardahl technologies and the best formulation solutions available, they ensure significantly higher performance than conventional oils and an additional performance reserve compared to standards.

Bardahl Polar Plus + Fullerene:

- Allows maximum engine protection even under critical lubrication circumstances, as well as significant reduction of wear.

MCO Tailored Chemistry System:

- The innovative 4-stroke motorcycle engines specific additivation allows to maximize engine, transmission and clutch efficiency, while providing total protection to all lubricated mechanical parts.
- Thanks to the balanced level of friction provided, it allows superior performance and durability of the clutch, as well as correct transfer of motion from the engine to the gearbox, for the benefit of greater acceleration and power.
- Allows to prevent the accumulation of deposits on the hottest parts of the engine and to counteract the damaging of gearbox from wear and pitting.

Radial Polymer Structure - High Shear Stability:

- The radial structure polymer employed, having high Shear Stability, ensures excellent performance in terms of tenacity of the lubricating oil film even in the most critical conditions of use. Minimizes lubricant's viscosity loss due to mechanical shear stress that occurs during operation, especially within the gearbox. It allows the formulation to maintain its viscosimetric properties over time and to maintain pumpability at low temperature, providing advantages in terms of protection from wear and prolonging the oil's lifespan.

Advanced Synthetic Blend:

- Formulated with synthetic and highly refined bases at high viscosity index.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



ADVANCED SYNTHETIC BLEND

Product Data Sheet

SAE 10W-30

Improves engine performance, allowing for a greater efficiency.
Suitable for engines that specifically require lower viscosity lubricants.

SAE 10W-40

Ensures maximum engine protection even in the most critical conditions of lubrication, while allowing excellent energy efficiency.

SAE 10W-50 and 15W-50

Ensure maximum engine protection even in the most critical conditions of lubrication. Particularly suitable where a greater control of oil viscosity decay caused by excessive temperature rise and fuel dilution is needed. Allow to minimize oil consumption.

PERFORMANCE LEVEL

API SN, JASO MA / MA2

CHEMICAL-PHYSICAL CHARACTERISTICS

SAE	Viscosity 40°C cSt	Viscosity 100°C cSt	Density 15°C kg/l	Viscosity Index	Flash Point	Pour Point	T.B.N. mg KOH/g
10W-30	76,1	11,3	0,867	139	207	-42	7,1
10W-40	92,6	13,6	0,867	148	210	-42	10,7
15W-50	143,7	18,5	0,871	145	211	-42	7,7
20W-50	169,1	19,6	0,874	134	211	-36	7,8

Values mentioned in this table are indicative and variable within certain tolerances

STORAGE

Store in the original closed packaging, maintaining it indoors, protected from moisture, direct exposure to sunlight and weather conditions. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio