



FULLY SYNTHETIC SPECIAL OIL

## Product Data Sheet

**Premium Performance** lubricant, completely synthetic, specific for 4-stroke Scooter and Maxi-Scooter engines, air or liquid cooled.

### Superior Performance – Total Protection

Bardahl advanced technology, thanks to the exclusive Polar Plus + Fullerene formula and the 4-stroke motorcycle engines “ad hoc” additivation, **MCO Tailored Chemistry System**, provides total engine protection allowing greater efficiency and power. Bardahl lubricants ensure significantly higher performance than conventional oils.

- Counteracts the formation of deposits for maximum engine cleanliness
- Suitable for both urban “stop and go” use and long distances
- Ensures top lubrication efficiency even under high stress conditions
- Formulated with special polymers with very high resistance – Radial Polymer Structure
- 100% Synthetic Formula

### PERFORMANCE LEVEL

API SN, JASO MA / MA2

### CHEMICAL-PHYSICAL CHARACTERISTICS

SAE	Viscosity 40°C cSt	Viscosity 100°C cSt	Density 15°C kg/l	Viscosity Index	Flash Point	Pour Point	T.B.N. mg KOH/g
5W-40	87,5	14,2	0,854	169	212	-45	8

*Values mentioned in this table are indicative and variable within certain tolerances*

### STORAGE

Store in the original closed packaging, maintaining it indoors, protected from moisture, direct exposure to sunlight and weather conditions. Avoid continuous and excessive temperature changes.

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio