



Product Data Sheet

Quality Performance lubricant specific for 4-stroke Scooter and Maxi-Scooter engines, air or liquid cooled.

Superior Performance – Total Protection

Bardahl advanced technology, thanks to the exclusive Polar Plus + Fullerene formula and the 4-stroke motorcycle engines “ad hoc” additivation, **MCO Tailored Chemistry System**, provides total engine protection allowing greater efficiency and power. Bardahl lubricants ensure significantly higher performance than conventional oils.

- Counteracts the formation of deposits for maximum engine cleanliness
- Suitable for both urban “stop and go” use and long distances
- Ensures top lubrication efficiency even under high stress conditions
- Formulated with special polymers, Radial Polymer Structure, at very high Shear Stability

SAE 5W-40 FULLY SYNTH

Ensures maximum engine protection even in the most critical conditions of lubrication, while allowing excellent energy efficiency.

Particularly suitable for engines that specifically require extremely fluid lubricants.

100% Synthetic formula.

SAE 10W-40 ADVANCED SYNTHETIC BLEND

Ensures maximum engine protection even in the most critical conditions of lubrication, while allowing excellent energy efficiency.

PERFORMANCE LEVEL

API SN, JASO MA / MA2

CHEMICAL-PHYSICAL CHARACTERISTICS

SAE	Viscosity 40°C cSt	Viscosity 100°C cSt	Density 15°C kg/l	Viscosity Index	Flash Point	Pour Point	T.B.N. mg KOH/g
5W-40	88,2	14,5	0,853	171	210	-45	8
10W-40	92,5	13,5	0,867	148	210	-42	8

Values mentioned in this table are indicative and variable within certain tolerances

STORAGE

Store in the original closed packaging, maintaining it indoors, protected from moisture, direct exposure to sunlight and weather conditions. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio