



Product Data Sheet

Quality Performance lubricant specific for 4-stroke Scooter and Maxi-Scooter engines without wet clutch, air or liquid cooled, requiring low viscosity lubricants that meet JASO MB performance specifications.

Superior Performance – Total Protection

Bardahl advanced technology, thanks to the exclusive Polar Plus + Fullerene formula and the 4-stroke motorcycle engines “ad hoc” additivation, **MCO Tailored Chemistry System**, provides total engine protection allowing greater efficiency and power. Bardahl lubricants ensure significantly higher performance than conventional oils.

- Counteracts the formation of deposits for maximum engine cleanliness
- Suitable for both urban “stop and go” use and long distances
- Power Improver: greater engine efficiency and fuel economy, maximizing performance
- Ensures top lubrication efficiency even under high stress conditions
- Formulated with special polymers, Radial Polymer Structure, at high Shear Stability
- 100% Synthetic Formula

PERFORMANCE LEVEL

API SN, JASO MB

CHEMICAL-PHYSICAL CHARACTERISTICS

| SAE | Viscosity 40°C cSt | Viscosity 100°C cSt | Density 15°C kg/l | Viscosity Index | Flash Point | Pour Point | T.B.N. mg KOH/g |
|--------|-----------------------|------------------------|----------------------|--------------------|-------------|------------|--------------------|
| 10W-30 | 67,1 | 11 | 0,852 | 154 | 218 | -45 | 8 |

Values mentioned in this table are indicative and variable within certain tolerances

STORAGE

Store in the original closed packaging, maintaining it indoors, protected from moisture, direct exposure to sunlight and weather conditions. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio