

Gear Oil 4005 SAE 75W-90

Product Sheet

Gear Oil 4005 75W-90 is a Total Driveline fully synthetic oil, developed for lubricating the manual transmissions and the differential units of standard vehicles, sports cars and commercial vehicles.

Its extraordinary E.P. (Extreme Pressure) properties and its excellent resistance to degradation from use make it suitable for strongly stressed hypoid differentials and for gear systems exposed to high temperatures for a long time.

PROPERTIES

- Best protection of gears against wear and strong loads.
- Improved efficiency of transmission.
- Ensures longer life and cleanliness for all parts of transmission.
- High resistance against degradation and thermal oxidation.
- Compatible with synchronizers and elastomers.
- Helps to extend the oil change interval as indicated by manufacturer.



Gear Oil 4005 SAE 75W-90

Product Sheet

PERFORMANCE LEVEL

API GL-4 / GL-5 / MT-1, SAE J2360, MIL-PRF-2105E, MB 235.8, MACK GO-J, MAN 341-E3 / 341-Z2 / 342-S1, SCANIA STO 1:1G / 2:0 A FS, VOLVO 97312, ARVIN MERITOR O-76-E / O-94, RENAULT B0032/2 annex 3, DAF, IVECO, ZF TE-ML 02B / 05A / 05B / 07A / 08 / 12B / 12L / 12N / 16F / 17B / 19C / 21B / 21A

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity at 40°C	108,7 cSt
Viscosity at 100°C	16,2 cSt
Density at 15°C	0,869 kg/l
Viscosity Index	161
Flash Point	146°C
Pour Point	<-36°C

The values shown in this table are just as an indication, variable within certain tolerances.

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.