



# ATF Speed D III G

## Product Sheet

**ATF Speed D III G** is a fluid expressly formulated to be used in automatic transmissions and in the hydroguide of cars and commercial vehicles for which the manufacturer prescribes ATF type GM D-IIIG level fluids.

### Superior Performance - Total Protection

The special additives used give the product a high thermal-oxidative stability and resistance to deterioration. Its marked rheological properties, a high viscosity index and high cold fluidity allow maximum efficiency of the transmission at both low and high temperatures. The excellent anti-wear, anti-foam and durability of clutch performance characteristics allow maximum protection of mechanical components, superior driving comfort and transmission efficiency.

### PROPERTIES

- Improved transmission efficiency.
- Maximum gear protection against wear.
- Longer life and cleanliness of all transmission parts.
- High resistance against thermal degradation and oxidation.

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



## ATF Speed D III G

### Product Sheet

#### PERFORMANCE LEVEL

<b>Allison C-4</b>
<b>CAT TO-2</b>
<b>Ford M / TASA</b>
<b>GM D-IID / D-IIE / D-IIIG</b>
<b>MAN 339 V1 / Z1</b>
<b>MB 236.9</b>
<b>Voith H55.6335</b>
<b>Volvo 97340 / 97341</b>
<b>ZF TE-ML 03D / 04D / 09 / 14A / 17C</b>

#### CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity at 40°C	36.21 cSt
Viscosity at 100°C	7.46 cSt
Density at 15°C	0.854 g/cm <sup>3</sup>
Viscosity index	179
Flash point	196°C
Pour point	-51°C
Colour	Light red
Brookefield -40°C	14597 mPa.s

*The values shown in this table are just as an indication, variable within certain tolerances.*

#### STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.

#### Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542  
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio