



ATF X-Speed Multivehicle

Product Sheet

ATF X-Speed Multivehicle is a completely synthetic fluid, Universal Multi-Vehicle, formulated to be used in automatic car transmissions, either on the latest generation with a high number of gears (6 and more), and technologically less recent at 3, 4 and 5 gears for which the manufacturer prescribes highly performing ATF fluids.

Superior Performance - Total Protection

The special additives used give the product a high thermal-oxidative stability, prevent the lubricant from deterioration and allow longer intervals between oil changes. Its marked rheological properties, a high viscosity index and high cold fluidity allow maximum efficiency of the transmission at both low and high temperatures. The excellent anti-wear, anti-foam and durability of clutch performance characteristics allow maximum protection of mechanical components, superior driving comfort and transmission efficiency.

PROPERTIES

- Improved transmission efficiency, excellent fuel-economy properties.
- Maximum gear protection against wear.
- Superior resistance against degradation and thermal oxidation, keeps the transmission clean and every part lubricated.
- Consistent performance over time and at extreme environmental temperatures.
- It allows to extend the oil change interval as much as foreseen by the manufacturer.
- Maximum usage flexibility.
- Formulated completely with synthetic bases.

The special universal formulation allows the product to be used in maximum safety both in applications requiring low viscosity fluids and in those requiring higher viscosity fluids, with the guarantee of always obtaining maximum transmission efficiency and total protection of all the lubricated components. This peculiarity has been made possible through the development of particular additives and the use of high-quality synthetic bases with high viscosity index (PAO and HC plus) which allow to obtain excellent cold fluidity and superior resistance of the oil film at high temperatures and stresses.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



ATF X-Speed Multivehicle

Product Sheet

ATF X-Speed Multivehicle is suitable for use where the specifications, product codes or products shown in the table are required.

Suitable for use - high viscosity	Suitable for use - low viscosity
Allison C-4	
ATF Esso LT 71141 / JWS 3309 / Mobil ATF 3309 / Shell 3403-M115 / Shell LA 2634 / Texaco ETL 7045E / Texaco ETL 8072B / Texaco N402	Shell 134 / Shell 3353 / Shell M-1375.4 / ZF Lifeguard fluid 6 / 6 Plus / 8 / 9
Audi - VW G 052 025 A2 / G 052 055 / G 052 162 (-A1, -A2) / G 052 533 / G 052 990 (A2) / G 055 025 (A2) / G US 000 162	G 055 005 (-A, A2) / G 055 540 (A2) / G 060 162 (-A1, -A2, -A6)
Bentley	P/N PY112995PA
BMW - MINI P/N 81 22 9 400 272 / 275 / 81 22 9 407 858 / 859 / 83 22 0 024 359 / 83 22 0 026 922 / 83 22 0 402 413 / 83 22 0 403 248 / 83 22 0 403 249 / 83 22 7 542 290 / 83 22 9 407 765 / 83 22 9 407 807	P/N 83 22 0 142 516 / 83 22 0 397 114 / 83 22 2 152 426 / 83 22 2 163 514 / 83 22 2 289 720 / 83 22 2 305 396 / 83 22 2 305 397
Chrysler - Dodge - Jeep +3 / +4 / SP-III / AS68RC ATF	P/N 05127382AA / 68043742AA / 68157995AA
MB 236.3 / 236.5 / 236.6 / 236.7 / 236.8 / 236.9 / 236.91 / 236.10 / 236.11	236.12 / 236.14 / 236.15 (except for the provided fuel economy benefits) / 236.16 / 236.17 / 236.41
FIAT	9.55550-AV5
Ford - Lincoln - Mercury WSS-M2C922-A1 / P/N XT-2-QDX [M] / XT-2-QSM [Syn] / XT-5-QM / -DM [V] / XT-8-QAW [Premium] / XT-9-QMM5 [FNR5]	P/N XT-10-QLV [LV] / XT-6-QSP / -DSP [SP]
GM - GMC - Opel Dexron II / IID / IIE / IIIG / IIIH / Type A Suffix A / Type T-IV / P/N 12378515 [Synthetic] / 19 40 700 / 19 40 767 / 21005966 Transaxle / 22717466 / 88900925 / 9986195	AW1 / Dexron VI / P/N 88863400 / 88863401
Honda - Acura Z-1	DW-1
Hyundai - Kia ATF Red-1K / JWS-3309 T-4 / SP-II / SP-III / P/N UM040 CH20 Red-1	NWS-9638-T-5 / SP-IV / SPH-IV / P/N 040000C90SG
Idemitsu ATF HP / K17	
Isuzu ATF II / ATF III / P/N 08200-9001	
Jaguar JLM 20238 / JLM 20292 / JLM 21044 / K17	Fluid 8432 / 02JDE 26444
JASO M315 / Class 1A	
Land Rover Esso Type LT 71141 / Texaco ETL 7045E	P/N TYK500050 / LR023288

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



ATF X-Speed Multivehicle

Product Sheet

MAN 339 A	
MASERATI	P/N 231603
Mazda F1 / M-III / M-V / Type T-IV	FZ
Mitsubishi ATF-J2 / SP / SP-II / SP-III / P/N MS991156	ATF-J3
Nissan - Infinity Matic-D / Matic-J / Matic-K / Matic-W	Matic-S
Porsche P/N 000 043 204 41 / 000 043 205 09 / 000 043 205 28 / 999 917 547 00 (A2)	P/N 000 043 304 00
Peugeot - Citroën P/N Z 000169756	
Renault Matic D2	
Saab 3309-T-IV	P/N 93 165 147-AW-1
SSANG YONG DSIH 5M-66	
Subaru HP / P/N K0140Y0700	
Suzuki 3314 / 3317	
Toyota - Lexus - Scion Type D-II / Type T / Type T-III / Type T-IV	Type WS
Volvo P/N 1161521 / 1161540 / 1161640	
Volvo Constr. Equip. (VCE) 1273-41	
ZF TE-ML 11A / 11B	

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity at 40°C	29.72 cSt
Viscosity at 100°C	6.30 cSt
Density at 15°C	0.838 g/cm ³
Viscosity index	164
Flash point	203°C
Pour point	-51°C
Colour	Light red
Brookfield a -40°C	7279

The values shown in this table are just as an indication, variable within certain tolerances.

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio