



BRAKE FLUID DOT 4

Product Sheet

Bardahl Brake Fluid DOT 4 is a synthetic fluid for disc and drum brake hydraulic systems and clutch, of both cars and motorcycles, with high stability properties at high temperatures, which ensure extreme safety in use. Also suitable for all vehicles equipped with ABS systems.

The high boiling point, both in dry and wet conditions, allows the product to be used in complete safety even in case of particularly high temperatures, without the likelihood of the formation of dangerous vapor bubbles within the fluid (Vapor Lock phenomenon). Its excellent fluidity when cold, on the other hand, allows it to be used even at the lowest environmental temperatures.

Bardahl Brake Fluid DOT 4 is not corrosive towards metals present in hydraulic systems and does not cause swelling of the rubber parts with which it is in contact (even permanently), thus helping to avoid problems with the seals generally present in braking systems.

Its considerable lubricating power favors the proper functioning of the mechanical parts present in hydraulic circuits and helps to reduce the wear of moving parts.

Bardahl Brake Fluid DOT 4 by virtue of its high chemical stability, makes the product unalterable even under the effect of particularly intense thermal stress.

- Excellent thermal stability and high safety against the Vapor Lock phenomenon
- Compatible with all rubbers, both natural and synthetic
- High anticorrosive protection on metals
- 100% Synthetic Formula

PRECAUTIONS FOR USE

Always follow the vehicle manufacturer's instructions.

Keep the brake fluid in its original container and well closed to prevent moisture absorption. The absorbed moisture significantly decreases the boiling point of the fluid, thus favoring the creation of steam bubbles thus reducing the braking effectiveness of the system.

The fluid can damage paint. Not compatible with mineral and silicone fluids.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



BRAKE FLUID

DOT 4

Product Sheet

CLAIMS

SAE J1704, FMVSS 571.116 DOT 4 and ISO 4925 Class 4

CHEMICAL-PHYSICAL CHARACTERISTICS

Property	Bardahl Brake Fluid DOT 4
Viscosity at -40°C in mm ² /s	1350
Viscosity at 100°C in mm ² /s	2,3
Boiling point (dry) in °C	260
Boiling point (wet) in °C	168
pH	8,7

The values shown in this table are just as an indication, variable within certain tolerances.

STORAGE

Store in original closed packaging, store indoors, away from moisture, from direct exposure to sunlight and weather. Avoid continuous and excessive temperature changes.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio