



Antifreeze HOA Tech Concentrate

Product Sheet

Concentrated cooling and antifreeze liquid, based on pure **non-regenerated** ethylene glycol. Proper for cooling circuits of cars, motorcycles and commercial vehicles which require premium fluids of HOAT type (Hybrid Organic Acid Technology). Protects the whole cooling system (radiators, cylinders, cylinder heats and water pumps) from overheating, corrosion and encrustation. Suitable for new generation engines with parts in aluminium alloy and engines of a less recent generation. Free from nitrites, amines and phosphates.

INSTRUCTIONS FOR USE: Use the product once it has been diluted with demineralized water. Diluted at 50% in volume permits a freezing point of approximately -37°C and a boiling point of approximately 108°C. Abstain from mixing with fluids of a different technology. See the use manual of the manufacturing company, previously.

It is compatible with hard waters. Do not use flowing back waters, originating from industrial processes, or brackish waters.

VALUES OF WATER COMPOSITION

Hardness	170 ppm MAX (come CaCO ₃)
Chlorides	40 ppm MAX
Sulphates	100 ppm MAX
Total Solids	340 ppm MAX
pH	5,5 - 9

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio



Antifreeze HOA Tech Concentrate

Product Sheet

TABLE OF DILUTION

Bardahl Antifreeze HOA Tech	Water	Freezing Point
1	2	-18 °C
1	1,5	-27 °C
1	1	-37 °C

PERFORMANCE LEVEL

ASTM D 3306 / D 4985, SAE J1034, CUNA NC 956 – 16, B.S. 6580:2010, AFNOR NF R15-601, NATO S 759, VW TL 774-C (SFU G11), MB 325.0, MTU MTL 5048, MAN 324 NF

CHEMICAL-PHYSICAL CHARACTERISTICS

Color	Blue-Green
Look in water solution	Clear, free from suspended particles
Solubility in water	Complete
Density at 20°C	1,110 – 1,145 kg/l
Water	5% Max
Alkaline reserve	11 ml HCl 0.1 N Min
Freezing Point (50% Volume)	-37°C
pH (water solution 50%)	7,5 Min
Compatibility with hard waters	Compatible

The values shown in this table are just as an indication, variable within certain tolerances.

STORAGE

If stored and kept in its original containers and hermetically sealed, at a temperature not higher than 30°C, **Antifreeze HOA Tech Concentrate** has a life of at least 3 years.

Do not store the product in galvanized containers.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio